

# GP3188

## Easy Usage, Great Affordability

### SPECIFICATION SHEET

Two-Way Radio

GP3188 Conventional Portable



## KEY ATTRIBUTES AND FEATURES

### Crystal Clear Audio

Exceptional audio design for that added communications edge.

### Extended Talktime

19hr-talktime on low power and 14hr-talktime on high power for greater productivity.

### Battery Latch Lock Feature

Keeps the power source firmly fastened to the radio and allows continuous communication.

### Durable and Reliable

Compliant with demanding MIL-STD 810 standards, thus apt for harsh working environments.

### Compatible Accessories

Compatible with existing original Motorola and MagOne accessories, thus protecting your investment.

### Quick and Easy Programming

Faster programming with the user-friendly Microsoft Windows® based Customer Programming Software.

## UNIQUE FEATURES

All features of the GP3188 are available through a single Toggle button. Remarkably clear and reliably rugged, the GP3188's ergonomic design also adds a touch of style.

### Voice Operated Transmission (VOX)

Provides total handsfree for maximal productivity.

### Battery Indicator

LED provides status of battery life at a glance.

### Sticky Permanent monitor

Allows user to stay on monitor mode without consistently pressing the programmable button.

## IDEAL FOR:

### SECURITY

Call for backup with just a simple, one-button operation of the GP3188. Faster response to emergency situations and intruders means a job well done.

### HOSPITALITY

Get compliments, not complaints with prompt, proactive levels of service, thanks to the handy GP3188. Slim, easy to carry around and hands free operation enables staff to meet guest's demands quickly.

### MANUFACTURING

Coordination with many people, even across different plants, can be done easily and quickly with the GP3188. Its extended talktime will easily last beyond 12-hour shift.

### CONSTRUCTION

A harsh environment requires a hardy radio. The GP3188 meets stringent Military Standards 810 C, D, E and F for durability; and loud 500mW speaker ensures clear audio even in high noise environments.

## TECHNICAL SPECIFICATION

### GP3188 Specifications \*

General	VHF		UHF	
Frequency	136-162MHz, 146-174MHz		403-440MHz, 438-470MHz, 465-495MHz	
Channel capacity	16 channels			
Power supply	7.5V±20%			
Dimensions (without belt clip and antenna)				
With NiCd/extended Lilon	126.5mm (H) x 61.5mm (W) x 45mm (D)			
With standard NMH	126.5mm (H) x 61.5mm (W) x 43mm (D)			
With slim Lilon	126.5mm (H) x 61.5mm (W) x 42mm (D)			
Weight (without belt clip and antenna)				
With extended Lilon	351g			
With slim Lilon	350g			
With standard NMH	417g			
With NiCd	406g			
Average Battery Life@ 5-5-90 Duty Cycle	Hi Power (5W)	Low Power (1W)	Hi Power (4W)	Low Power (1W)
With extended Lilon	14hrs	19hrs	14hrs	19hrs
With slim Lilon	12hrs	17hrs	12hrs	17hrs
With standard NMH	10hrs	13hrs	10hrs	13hrs
With NiCd	8hrs	10hrs	8hrs	10hrs
<b>Receiver<sup>+</sup></b>	<b>VHF 12.5 kHz</b>	<b>VHF 20/25kHz</b>	<b>UHF 12.5 kHz</b>	<b>UHF 20/25kHz</b>
Frequency	136-162MHz, 146-174MHz		403-440MHz, 438-470MHz, 465-495MHz	
Sensitivity 12dB EIA SINAD	0.25uV		0.25uV	
Adjacent Channel Selectivity	-65dB	-70dB	-60dB	-70dB
Intermodulation	-70dB		-70dB	
Frequency Stability (-30°C to +60°C)	0.00025%		0.00025%	
Spur Rejection	-75dB		-75dB	
Hum and Noise	-45dB@12.5kHz		-50dB@25kHz	
Image and 1/2 I-F Rejection	-70dB		-70dB	
Audio Output @ < 5% Distortion	500mW		500mW	
<b>Transmitter</b>	<b>VHF</b>	<b>VHF</b>	<b>UHF</b>	<b>UHF</b>
Frequency	136-162MHz, 146-174MHz		403-440MHz, 438-470MHz, 465-495MHz	
Channel Spacing	12.5/20/25kHz		12.5/20/25kHz	
Frequency Stability (-30°C to +60°C)	0.00025%		0.00025%	
Spurs/Harmonics	-36 dBm < 1GHz		-36 dBm < 1GHz	
	-30 dBm > 1GHz		-30 dBm > 1GHz	
Audio Response (from 6dB/oct. Preemphasis, 300 to 3000Hz)	+1, -3dB		+1, -3dB	
Audi Distortion @1000Hz, 60% Rated Max. Dev.	<3%		<3%	
FM Noise	-40dB(12.5Khz)		-40dB(12.5Khz)	
	-45dB(25Khz)		-45dB(25Khz)	
FCC Modulation 20/25 kHz	16K0F3E & 11K0F3E		16K0F3E & 11K0F3E	

\* Availability subject to country's laws and regulations. Radios meet applicable regulatory requirements.  
All specifications subject to change without notice.  
Specifications are not representative of all radios and may vary in different radios.  
+ All RF readings are typical.

### ACCESSORIES FOR GP3188



NNTN4970A -  
Slim Lilon  
Battery

HMN9021A -  
Medium Weight  
Dual-Muff  
Headset with  
Swivel Mic

RLN5238A -  
Sports-Style  
Headset with in-  
line PTT

BDN6646C -  
Ear Microphone  
with PTT  
Interface Module

PMLN4606A -  
2Wire  
Surveillance Kit  
with Clear  
Acoustic Tube

## ENHANCE YOUR RADIO'S CAPABILITIES

A comprehensive range of accessories is available to suit your needs. With the right combinations of batteries, headsets, carry cases and antenna, it can increase your operational productivity and comfort tremendously. Motorola original accessories are built with the highest quality standards and are specially engineered to ensure maximum performance of your radio.

### Programmable Features

- High/Low Power
- System Scan
- Monitor
- Tight/Normal Squelch
- Repeater/Talkaround

### ACCESSORIES #

#### BATTERIES

Standard NiMH Battery, 1400mAh  
NNTN4851A

Slim Lilon Battery, 1600mAh  
NNTN4970A

Extended Lilon Battery,  
1800mAh  
NNTN4497AR

NiCd Battery, 1100mAh  
NNTN4496AR

SINGLE & MULTI UNIT  
CHARGERS

Desktop Rapid Charger w/US NA  
Plug  
WPLN4138\_R

Desktop Rapid Charger w/Euro Plug  
WPLN4139\_R

Desktop Rapid Charger w/UK Plug  
WPLN4140\_R

Rapid Charger MUC 120V w/US  
Plug  
WPLN4161AR

Rapid Charger MUC 220V w/Euro  
Plug  
WPLN4162AR

Rapid Charger MUC 220V w/UK  
Plug  
WPLN4163AR

# Motorola carries a wide range of audio and carrying solution.  
Please refer to specified accessories brochures for more information.



**Motorola Electronics Pte Ltd**  
MIC Level 7, 12 Ang Mo Kio Street 64  
Ang Mo Kio Industrial Park 3, Singapore 569088  
www.motorola.com/governmentandenterprise

MOTOROLA and the Stylized M Logo are registered in the U.S. Patent and Trademark Office.  
All other products or service names are the property of their registered owners. ©Motorola, Inc. 2006  
AC3-04-021 Rev.4



Stingray Motorola  
Accelerated Life Testing  
simulating five years of hard  
use in real life. EIA RS-216  
in Shock, Vibration, Dust,  
Humidity, IP54 for Sealing.



Compliance with ISO 9001  
Standard on international quality  
system assurance on design,  
development, production,  
installation and servicing of a  
product.



Stamp of Approval from  
the U.S. Military for use  
in rough environment.





# *A Rugged Radio for Harsh Environments*

Motorola GP628 Plus and GP638 Plus are IP67-rated\*  
dust-tight and water submersible





## Standing up to the challenge

Imagine this scenario – The shrill scream of the fire alarm pierced the night. Within minutes, nine men assembled outside a fire engine awaiting instructions.

“This is no ordinary fire,” cautioned the fire chief. “We are dealing with a burning manufacturing plant, and its storage area contains tanks which may explode if burned, so please make sure you are carrying the correct communications equipment today.” The fire fighters checked their Motorola GP628 Plus radios briefly, noting the prominent green dot on the Li-ion battery pack, which identifies it as an FM-rated battery.

As they arrived at the fire scene, its extent became clear. Burning goods crackled noisily amongst the shouts of frightened plant workers. Hearing one another was going to be difficult.

The fire chief pulled on his helmet, oxygen tank and protective gloves. He was thankful for the lightweight radios – it was important not to burden his men any more than necessary. Easily finding the sculpted Push-to-Talk (PTT) button even with his gloved hands, he addressed his men.

“Fan out into 3 teams. Team Alpha, go around the back to make sure the fire does not spread to the chemicals warehouse. Team Beta, control the fire in front and around the sides. Team Charlie, follow me inside for rescue operations. Over and out,” the fire chief spoke calmly into his radio. He knew he did not need to shout to make himself heard, given the audio clarity from the GP628 Plus radio.

Visibility rapidly deteriorated once they were inside the burning building. Out of the corner of his eye, the fire chief sensed something looming over him. “Collapse!” he shouted, as he and his men dived away just a split second before a 20-foot wall crumbled before them.

Picking up his axe, he searched around for his radio, and found it lying in a pool of muddy water. This did not bother him one bit – he knew the GP628 Plus was IP67-rated water submersible, thanks to its ruggedised casing. Moreover, the IP67-rated dust-tight and water submersible radio is designed and built to globally-recognised FM and MIL standards.

## A Rugged Radio for Harsh Environments

Introducing the Motorola GP628 Plus non-keypad and the GP638 Plus keypad radios, the toughest from Motorola to date. Rated IP67 dust-tight and water submersible, the radios are also resistant to knocks and drops, thanks to their ruggedised exteriors. The GP628 Plus and the GP638 Plus feel right at home in the dangerous, extreme world of emergency rescue operations.

Lightweight and compact, Motorola’s smallest professional two-way radios have received Factory Mutual (FM) Approval and meet Military Standards (MIL) 810C, D, E and F.



IP67 Rated and FM Approved  
GP628 Plus

IP67 Rated and FM Approved  
GP638 Plus

## Users

### Fire Rescue Operations

The Motorola GP628 Plus and GP638 Plus are lightweight and compact and will not hamper you during rescue operations. Durability is ensured with IP67-rated protection against dust and water. Simple, programmable buttons enable lightning-fast communications during tense situations. A specially sculpted ergonomic PTT button, similarly IP67-rated, ensures easy operation even with gloved hands.

### Manufacturing

The rugged exterior of the GP628 Plus and GP638 Plus conform to stringent Factory Mutual (FM) and Military Standards 810C, D, E and F, making them suitable for operation in potentially sensitive environments such as petrochemical and manufacturing plants. The radios have been subjected to Motorola Accelerated Life Testing (ALT) which ensures that they can withstand drop/shocks, rain, salt, fog, electro-static discharge and flame.

### Rescue Operations

The IP67-rated GP628 Plus and GP638 Plus are suitable for use in typhoons, earthquakes and flood relief operations. Rescue personnel already burdened with heavy equipment and protective gear will appreciate the compact size, light weight and ergonomic design of the radios.

## GP628 Plus and GP638 Plus Key Features and Benefits

### Dust-tight, water submersible, lightweight and rugged

#### Advanced Audio Technology

Motorola's voice compression and low level expansion technology enable crisp, clear and loud audio, allowing you to keep communicating during critical operations.

#### Emergency Alarm / Siren

An easily-accessible, one-touch emergency button on the GP628 Plus or the GP638 Plus will emit a piercing alarm when pressed, for urgent communications in critical situations.

#### Switchable RF Power Levels

Adjusts the radio's transmitting power according to the user environment, and offers a choice between maximum coverage and battery conservation. High RF power increases transmission range, while low power conserves battery life.

#### Repeater / Talkaround Enable / Disable

Enjoy long-range communications via a repeater, or bypass it to communicate point-to-point. The talkaround feature is useful for maintaining communications lines when a repeater goes out of service.

#### Tight / Normal Squelch

Enhanced audio clarity is achieved by filtering out unwanted interference. A tight squelch gives clearer playback of messages, while a normal squelch increases coverage.

#### Other Features


- LED Battery Gauge
- Tone Tagging
- Internal VOX
- Priority Scan
- Enhanced Signalling Systems

### IP Code

The IP Code is a designation that indicates the level or amount of protection.

The IP Code designation consists of the letters **IP** (International Protection) followed by two numerals –

**example:**



## GP628 Plus – Compact & Easy to Use

Palm-sized and easy-to-use, any emergency-response team or fleet will be able to familiarise themselves quickly with the GP628 Plus. Its intuitive layout and programmable buttons offer fast responsiveness in emergency situations. Time saved equals lives saved.

### 16 Channels

Assign up to 16 channels for easy organisation of different work groups.

### LED Battery Gauge

An easily visible tri-colour battery gauge at the top of the radio provides battery level status at a glance. Green indicates a full battery; amber means half-full and red is a signal to recharge the battery.

### Tone Tagging

Allows assignment of 8 different ring tones to 8 specific users or talkgroups, for audio identification of these groups.

## Enhanced Signalling Features of GP628 Plus

GP628 Plus supports the following systems:

### MDC1200 Signalling

- PTT-ID (encode) – Identifies your outgoing calls during transmission, so verbal identification is not necessary
- Selective Call (decode) – Allows you to receive a specific group or individual call
- Call Alert (decode) – Notifies you of incoming calls
- Radio Check (decode) – Informs other workgroups that your radio is activated or within range
- Selective Radio Inhibit (decode) – If the radio is missing or stolen, the system owner can disable it remotely

### Quick Call II Signalling

### DTMF Signalling



## *A Rugged Radio for Harsh Environments*

Motorola GP628 Plus and GP638 Plus are IP67-rated\*  
dust-tight and water submersible



## GP638 Plus – Compact & Versatile

The GP638 Plus offers a versatile two-way solution for those who require additional features to meet their expanding communication needs. Whether you are in the rugged environment of the surveillance industry or in rescue operations, the GP638 Plus is the radio of your choice.

### 14-Character Alpha Numeric Dot Matrix display

The 14-character alpha numeric display allows immediate communication of vital information such as PTT ID, radio strength indicator and signal strength indicator. In addition, the user-friendly icons make the information easy to read and understand. The keypad and display illuminations also provide the needed visibility to operate your radio in the dark.

### Received Signal Strength Indicator

An easy to read on screen display indicator notifies users of signal strength in their vicinity.

### Name & Tone Tagging

The capability of assigning 8 different ringing tones and visual caller IDs to 8 specific users/talkgroups enhances audio and visual caller identification for these groups.

### Battery Strength Indicator

Easy to read on-screen LCD display indicator alerts users on low battery strength.

### 128 Channels

Provides up to a maximum of 128 channels, allowing greater flexibility in organising different work groups.

### Menu Keys

The easy to navigate menu keys allow users to select the relevant functionalities at their fingertips.

### Dual Tone Multiple Frequency (DTMF) Encode

Allows users easy access to local landline telephone networks or to make a private calls to other radio system users from one radio.

### Dual Priority Scanning

Allows activity on different channels to be monitored, and 2 channels can be designated as priority channels which are monitored more frequently.

## Enhance Your Radio's Capabilities

A comprehensive range of accessories is available so that the radio can be customised to suit your needs. Using it with the proper headsets, microphones, batteries, chargers or carrying cases can enhance your operational productivity. Motorola's accessories are specially engineered to ensure maximum performance of your radio, no matter what profession you are in.



**PMNN4073**

1350mAH FM Lilon Battery  
IP67-rated



**PMNN4074**

1400mAH Lilon Battery  
IP67-rated

## Enhanced Signalling Features of GP638 Plus

GP638 Plus supports the following signalling protocol:

### I) MDC1200 Signalling

#### PTT-ID (encode/decode)

Every time the PTT button is pushed, it enables the transmission of the caller's ID and the decoding of the sender's ID.

#### Status/Messages (decode)

This feature enables you to replace frequently used voice calls with status messages, saving you valuable communication time.

#### Call Alert (encode/decode)

If your call to a radio has no response, the radio will emit an alert tone until the other party takes action.

#### Voice Selective Call (encode/decode)

The radio users receive a unique individual or group voice message with an alert to indicate that it is a selective call.

### II) Quick Call II Signalling

### III) DTMF Signalling



**PMNN4023**

Remote Speaker Microphone  
IP57-Rated (Mic Head only)



Single-Unit Charger



Multi-Unit Charger

(order 6 battery inserts PMLN5010 separately, to charge IP67 radios in Multi-unit charger)

# A comprehensive range of accessories for GP628 Plus and GP638 Plus

## Antennas:

NAD6566	Antenna VHF Helical 136-150.8MHz
NAD6567	Antenna VHF Helical 150.8-162MHz
NAD6568	Antenna VHF Helical 162-174MHz
PMAD4056	Whip Antenna 330-368MHz
PMAD4057	Whip Antenna 370-400MHz
PMAE4022	Whip Antenna 403-470MHz
PMAE4025	Whip Antenna 450-527MHz



Earbud with combined Mic/PTT

## Single Unit Chargers:

PMTN4024	120V Single Unit Rapid Charger / US Plug
PMTN4025	230V Single Unit Rapid Charger / Euro Plug
PMTN4026	230V Single Unit Rapid Charger / UK Plug
HTN3006	230V Single Unit Rapid Rate Charger / Australia Plug



D-Shell RSM Earpiece

## Multi-Unit Chargers:

WPLN4187	Impres MUC, Non-Display, 110-230V, US Cord
WPLN4189	Impres MUC, Non-Display, 110-230V, EU Cord
WPLN4188	Impres MUC, Non-Display, 110-230V, UK Cord
WPLN4190	Impres MUC, Non-Display, Australia Cord
PMLN5010A	Multi-Unit Charger Insert (Required to charge radios with IP67 batteries)
WPLN4197	Impres MUC, Non-Display base only



D-Style Earset with Boom- Mic

## Batteries (capacity specified is typical value):

PMNN4074	Li-Ion 1400MAH, IP67 battery
----------	------------------------------

## Batteries - Intrinsically Safe (FM Approved) (capacity specified is typical value):

PMNN4073	Li-Ion 1350MAH, FM IP67 battery
(Rated Intrinsically Safe for use in Division 1, Classes I,II,III, Groups CDEFG and Nonincendive, Division 2, Class I, Groups ABCD).	


## Audio Accessories:

The following audio accessories are available for use with the radio in a non-IP67 environment.

The radio is only IP67 rated when used without audio accessories.

## Remote Speaker Microphones:

PMMN4022	Remote Speaker Microphone With 3.5 mm Audio Jack (IP54)
PMMN4023	Remote Speaker Microphone Without Audio Jack (IP57)



Ultra-Light headset w/Boom Mic and in-line PTT

## Optional Remote Speaker Microphone Accessories:

PMLN4620	D-Shell RSM Earpiece
----------	----------------------



Lightweight Headset w/Boom Mic and in-line PTT

## Standard Earpieces / Earsets:

BDN6781	Earbud (receive only)
PMLN4519	Earbud with Combined Mic/PTT
PMLN4657	D-Style Earset with Boom Microphone Tube
PMLN5002	D-Style Earpiece with Mic/PTT
BDN6780	Earbud with Combined Mic/PTT (requires PMLN4455)
NMN6246	Ultra-Light Headset w/ Boom Mic and in-line PTT, Earbud style receiver (requires PMLN4455)



Heavy Duty Noise Cancelling Boom Mic w/ PTT Earcup

## Headsets:

JMMN4066	Lightweight Headset w/ Boom Microphone and in-line PTT
RLN5590	Lightweight Headset w/ Boom Microphone (VOX compatible)
BDN6645	Heavy Duty Noise Cancelling Boom Mic Headset w/ PTT Earcup (requires RKN4093)
BDN6635	Heavy Duty Noise Cancelling Boom Mic Headset w/Vox (requires RKN4093)
NMN6245	Lightweight Single Muff Adjustable Headset w/Swivel Boom Mic and in-Line PTT switch (requires PMLN4455)
PMLN4585	Temple Transducer Headset
RMN5015	Racing Headset - Heavy Duty, Behind the Head Headset with Noise Cancelling Swivel Boom Microphone (requires RKN4093)



Temple Transducer Headset

Racing Headset - Heavy Duty

**Surveillance Kits:**

PMLN4608	2-Wire Surveillance Kit with Clear Acoustic Earpiece
PMLN4605	Clear Acoustic Earpiece (For PMLN4294, PMLN4418, PMLN4519)
PMLN4998	2-Wire Surveillance Earpiece w/ Combined Mic/PTT, Beige
PMLN4999	2-Wire Surveillance Earpiece w/ Combined Mic/PTT, Black
The following Surveillance Kits Requires PMLN4455 Adapter which attaches to the Radio. They are compatible with NTN8370 and NTN8371.	
The 2-W and 3-W kits are compatible with the RLN4922.	
BDN6664	Receive Only Earpiece Beige
BDN6726	Receive Only Earpiece Black
BDN6665	Receive Only Earpiece, Xtra Loud, Beige
BDN6727	Receive Only Earpiece, Xtra Loud, Black
BDN6666	Receive Only Earpiece with Volume Control, Beige
BDN6728	Receive Only Earpiece with Volume Control, Black
BDN6667	2-Wire Surveillance Earpiece w/ Combined Mic/PTT, Beige
BDN6729	2-Wire Surveillance Earpiece w/ Combined Mic/PTT, Black
BDN6669	2-Wire Surveillance Xtra Loud Earpiece w/ Combined Mic/PTT, Beige
BDN6731	2-Wire Surveillance Xtra Loud Earpiece w/ Combined Mic/PTT, Black
BDN6668	3-Wire Surveillance Earpiece w/ Separate MIC & PTT, Beige
BDN6730	3-Wire Surveillance Earpiece w/ Separate MIC & PTT, Black
BDN6670	3-Wire Surveillance Earpiece, Xtra Loud, w/ Separate MIC & PTT, Beige
BDN6732	3-Wire Surveillance Earpiece, Xtra Loud, w/ Separate MIC & PTT, Black
NTN8370	Extreme NoiseKit Clear Acoustic Tube
NTN8371	Low Noisekit Clear Acoustic Tube
RLN4922	Wireless Discreet Earpiece



Wireless Discreet Earpiece



Ear Mic VOX/PTT Interface Module

**Ear Microphone System:**

JMMN4064	Ear Microphone VOX/PTT Radio Interface Module
BDN6768	Standard Ear Microphone, Black (for noise levels up to 95dB)
BDN6769	Standard Ear Microphone, Beige (for noise levels up to 95dB)
BDN6770	High Noise Ear Microphone, Gray (for noise levels up to 105dB)
0180358B38	Remote PTT for Ear Microphone System (optional)
0180300E83	Remote Body Push-to Talk Switch for Ear Microphone System (optional)

Remote Body PTT Switch for Ear Mic



Remote Body PTT Switch for Ear Mic

**Audio Adapters:**

RKN4093	Radio Adapter Cable (required for indicated headsets)
PMLN4455	Audio Accessory Adapter (required for indicated audio accessories)

**Carry Accessories:**

JMZN4023	Plastic carry Holder with Belt clip
PMLN5089	Nylon Carry Case For Minnow IP67, Display
PMLN5090	Nylon Carry Case For Minnow IP67, Plain
JMZN4020	Hand Strap for radio
NTN5243	Shoulder Strap
HLN9985	Waterproof Bag



Surveillance Kits

### Portable Military Standards 810 C, D, E and F

Applicable MIL-STD	810 C		810 D		810 E		810 F	
	Methods	Procedures	Methods	Procedures	Methods	Procedures	Methods	Procedures
Low Pressure	500.1	1	500.2	2	500.3	2	500.4	2
High Temp	501.1	1, 2	501.2	1, 2	501.3	1, 2	501.4	1, 2
Low Temp	502.1	1	502.2	1, 2	502.3	1, 2	502.4	1, 2
Temp. Shock	503.1	1	503.2	1	503.3	1	503.4	1
Solar Radiation	505.1	1	505.2	1	505.3	1	505.4	1
Rain	506.1	1, 2	506.2	1, 2	506.3	1, 2	506.4	1, 3
Humidity	507.1	2	507.2	2, 3	507.3	2, 3	507.4	—
Salt Fog	509.1	1	509.2	1	509.3	1	509.4	—
Dust	510.1	1	510.2	1	510.3	1	510.4	1
Vibration	514.2	8, 10	514.3	1	514.4	1	514.5	1
Shock	516.2	1, 2, 5	516.3	1, 4	516.4	1, 4	516.5	1, 4

#### Factory Mutual Approval

The GP628 Plus and GP638 Plus radio units are certified by Factory Mutual Approvals as intrinsically safe for use in Division 1, Class I, II, III, Groups C,D,E,F,G and Division 2, Class I, Groups A,B,C,D, when ordered with the Factory Mutual approved battery option.



IP67 Rated and FM Approved  
GP628 Plus and GP638 Plus

### GP628 Plus and GP638 Plus Specifications

GENERAL SPECIFICATION	VHF / UHF		
**Frequency (MHz)	136-174 / 330-400 / 403-470 / 450-527		
Channel Capacity	16 Channels (GP628 Plus)	128 Channels (GP638 Plus)	
Power Supply	Provided through rechargeable battery	- 7.5V	
Dimensions (Radio footprint height excluding knobs)	<b>H</b>	<b>W</b>	<b>D</b>
	101.5 mm	56.5 mm	37 mm
Weight			
With LiIon (Hicap) Battery:	305 gm (GP628 Plus)	320 gm (GP638 Plus)	
Average Battery Life @ 5/5/90 Cycle	<b>Low Power</b>	<b>High Power</b>	
With LiIon (Hicap) Battery:	13 hours	10 hours	
Sealing	Withstands rain testing per MIL-STD 810 C/D/E/F and IP67		
Shock and Vibration	Protection provided via impact resistant housing exceeding MIL-STD 810 C/D/E/F and TIA/EIA 603		
Dust and Humidity	Protection provided via environment resistant housing exceeding MIL-STD 810 C/D/E/F and TIA/EIA 603		

### TRANSMITTER SPECIFICATION

	VHF / UHF		
**Frequency (MHz)	136-174 / 330-400 / 403-470 / 450-527		
Frequency Separation	Full bandsplit		
Channel Spacing	12.5 / 20 / 25kHz		
Freq Stability (-30°C to 60°C, +25°C Ref.)	2.5 ppm		
Power Output	5W (VHF) 4W (UHF)		
Modulation Limiting	±2.5 @ 12.5kHz, ±4.0 @ 20kHz, ±5.0 @ 25kHz		
FM Hum & Noise	-40 dB		
Conducted/Radiated Emission	-36 dBm < 1 GHz / -30 dBm > 1 GHz		
Modulation FCC Type	12.5 kHz 11K0F3E, 25 kHz 16K0F3E		
Audio Response	(from 6 dB/octave pre-emphasis 300-3000Hz)	+1 to -3 dB	
Audio Distortion	3%		

### RECEIVER SPECIFICATION

	VHF / UHF		
**Frequency (MHz)	136-174 / 330-400 / 403-470 / 450-527		
Frequency Separation	Full bandsplit		
Sensitivity (12dB SINAD) EIA	.25µV		
Intermodulation (EIA)	70 dB		
Adjacent Channel Selectivity	60 dB @ 12.5kHz, 70 dB @ 25 kHz		
Spurious Rejection	70 dB		
Rated Audio	500 mW		
Audio Distortion	3%		
Hum & Noise	-40 dB		
Audio Response (300-3000Hz)	+1 to -3 dB		
Conducted Spurious Emission	-57 dBm < 1GHz, -47 dBm > 1GHz, FCC Part 15		

\*\* Availability subject to country law and regulations.

Radios meet applicable regulatory requirements.

All specifications shown are subject to change without notice. Specifications are not representative of all radios and may vary in different radios. All Motorola products are manufactured under ISO 9001 standards and are subjected to Accelerated Life Testing (ALT). A series of stringent tests simulating five years of usage on the field, ALT ensures that the products survive drops/shocks, dust, rain, harsh chemicals and radiation.

Our Intrinsically Safe products meet formal safety agency certifications, such as Factory Mutual Research Corporation (FM) and Military Standard (MIL).

\* Dust-tight and water submersible are tested as per criteria in IEC (International Electrotechnical Commission) 60529 IP67



**MOTOROLA**





# GP328

The Power Tool for Contact & Control



## GP328 PORTABLE RADIO - A PRACTICAL RADIO

### KEY FEATURES AND BENEFITS

**X-PAND™ audio Technology**  
Motorola's special voice compression and expansion technology called X-PAND™ enables crisper, clearer and stronger audio quality, allowing you to keep communicating in any noisy environment.

#### 16 Channels

Maximum of 16 channels to organise work groups with ease and efficiency.

#### Tone Tagging

Assign 8 different ringing tones to 8 specific users/talkgroups making audio caller identification to these 8 groups possible.

#### LED Battery Gauge

Tri-colour LED to indicate battery strength, avoiding failed communication with early warning on low battery strength.

#### Emergency Siren

Easy-to-access, one-touch button with piercing alarm to seek help in critical situation.

#### Switchable RF Power Level

Optimise coverage and conserve battery consumption.

#### Field Retrofit Option Boards

Easy to install, affordable add-on functionality whenever your needs arise. Option Boards are available for:

- I) DTMF Decode for in-coming calls capability.
- II) Voice Storage for recording and playing back voice messages.

III) Mandown Alert for triggering an emergency procedure when the radio is horizontal or still for a predefined time. Ideal for radio users who work alone or in isolated environments

#### Programmable Channel Spacing Of 12.5/25 kHz Mode

Flexible and easy migration of channel spacing requirements in any situation.

#### Repeater/Talkaround Enable/Disable

Freedom to communicate via a repeater for wide area coverage; or bypass a repeater and talk directly to another unit for easy local unit-to-unit communications.

#### Internal Voice Operated Transmission (VOX)

For hands-free operation, activate this option by speaking with the optional headsets.

#### Tight/Normal Squelch

Flexibility to switch to tight squelch to filter out excessive noise; or, normal squelch for normal coverage.

The GP328 is the two-way radio solution for professionals who need to stay in contact but don't require extra features. This practical radio can easily increase productivity by keeping users communicating, yet streamlines their radio use—allowing them to concentrate on the job at hand. With the GP328, communication couldn't be easier.


#### Easy To Use, Lightweight Yet Rugged To Suit Your Every Need

Ideal when you need:

- Wide range coverage within the workplace.
- Simple-to-operate two-way radio.
- To contact people who are mobile.
- To make several calls to repeat the same message.
- To manage a facility or more than one building.

## ENHANCE YOUR RADIO'S CAPABILITIES

A comprehensive range of accessories is available so that the radios can be customised to suit your needs. Adding the proper headsets, microphones, batteries, chargers or carry cases can enhance your productivity. Motorola accessories are built with the highest quality standards and are specially engineered to assure maximum performance of your radio, no matter what profession you're in.



Light Weight Headset  
**AZRMN4018**



NiMH Battery  
**PMNN4008**  
Belt Clip  
**HLN9714** (order separately)



Carry Case  
**HLN9701**



Multi-Unit Charger  
**WPLN4187**  
(US Cord)  
**WPLN4188**  
(UK Cord)  
**WPLN4189**  
(Euro Cord)



Single Unit Charger  
**PMTN4024**  
(US Plug)  
**PMTN4025**  
(Euro Plug)  
**PMTN4026**  
(UK Plug)



Remote Speaker Microphone  
**PMMN4021**

## ENHANCED SIGNALLING FEATURES

The GP328 two-way radio supports these three Signalling protocols:

### I) MDC1200 Signalling:

- PTT-ID (encode)  
Identifies your outgoing calls on other users' radios
- Selective Call (decode)  
Lets you receive a specific group or individual call
- Call Alert (decode)  
Notifies you of incoming calls
- Radio Check (decode)  
Tell others if your radio is activated or within range
- Emergency (encode)  
Sounds an alarm or alerts dispatcher in urgent situations

### II) Quik Call II Signalling:

- Call Alert
- Voice Selective Call

### III) Dual Tone Multiple Frequency (DTMF)

Signalling Encode:

GP328 optional retrofit keypad model supports DTMF encode features

## OTHER GP328 FEATURES

- Channel Scan
- Time-Out-Timer
- PL / DPL
- Busy Channel Lockout

## ACCESSORIES SOLUTION

### Battery Options

Flexible choice of batteries:

- NiCD Battery
- High Capacity NiMH Battery
- Ultra High Capacity NiMH Battery
- Factory Mutual Approved NiCD & NiMH Batteries
- Lithium Ion Battery#

### Powerful **impres™** Smart Energy Solution

The **impres™** Smart Energy System helps battery maintenance, predicts end-of-service life and provides real-time battery usage information.

## GP328 Specifications\*

General Specifications							
*Frequency (MHz):	29.7 - 42 / 35 - 50 / 136 -174 / 330 - 400 / 403 - 470 / 450 - 527						
Channel Capacity:	16 Channels						
Power Supply:	Provided through rechargeable battery - 7.5V						
DIMENSIONS:							
With Standard High Capacity NiMH Battery:	H	x	W	x			
With Ultra High Capacity NiMH Battery:	137mm	x	57.5mm	x			
With NiCD Battery:	137mm	x	57.5mm	x			
#With Lilon Battery:	137mm	x	57.5mm	x			
	37.5mm 40.0mm 40.0mm 33.0mm (Radio footprint height excluding knobs)						
WEIGHT:							
With Standard High Capacity NiMH Battery:	420 gm						
With Ultra High Capacity NiMH Battery:	500 gm						
With NiCD Battery:	450 gm						
#With Lilon Battery:	350 gm						
AVERAGE BATTERY LIFE @ 5/5/90 CYCLE							
With Standard High Capacity NiMH Battery:	Low Power	High Power					
With Ultra High Capacity NiMH Battery:	11 hours	8 hours					
With NiCD Battery:	14 hours	11 hours					
#With Lilon Battery:	12 hours	9 hours					
With Lilon Battery:	11 hours	8 hours					
Sealing:	Withstands rain testing per MIL-STD 810 C/D/E/F and IP54						
Shock and Vibration:	Protection provided via impact resistant housing exceeding MIL-STD 810 C/D/E/F and TIA/EIA 603						
Dust and Humidity:	Protection provided via environment resistant housing exceeding MIL-STD 810 C/D/E/F and TIA/EIA 603						

## TRANSMITTER

Specifications	Low Band	VHF/UHF
*Frequency (MHz)	29.7 - 42 / 35 - 50	136 - 174 / 330 - 400 / 403 - 470 / 450 - 527
Frequency separation	Full bandsplit	
Channel spacing	12.5/20/25kHz	
Freq Stability: (-30°C to 60°C,+25°C Ref.)	+/- 0.0010%	+/- 0.00025%
Power	6W	5W - 136 - 174 4W - 330 - 400 / 403 - 470 / 450 - 527MHz
Modulation limiting	$\pm 2.5 @ 12.5\text{kHz}$ $\pm 5.0 @ 20\text{kHz}/25\text{kHz}$	$\pm 2.5 @ 12.5\text{kHz}$ $\pm 4.0 @ 20\text{kHz}$ $\pm 5.0 @ 25\text{kHz}$
FM Hum & Noise	-40dB	
Conducted/Radiated Emission	-36dBm < 1GHz / -30dBm > 1GHz	
Modulation FCC Type	12.5 kHz 11K0F3E / 25 kHz 16K0F3E	
Audio Response (from 6 dB/ octave pre-emphasis 300-3000Hz)	+1 to -3dB	
Audio Distortion	3%	

## RECEIVER

Specifications	Low Band	VHF/UHF
*Frequency (MHz)	29.7 - 42 / 35 - 50	136 - 174 / 330 - 400 / 403 - 470 / 450 - 527
Frequency separation	Full bandsplit	
Sensitivity (12dB SINAD)EIA	.25µV	
Intermodulation (EIA)	70dB	
Adjacent Channel Selectivity	60dB @ 12.5kHz / 70dB @ 25kHz	
Spurious Rejection	70dB	
Rated Audio	500 mW	
Audio Distortion	3%	
Hum and Noise	-45dB @ 12.5kHz, -50dB @ 25kHz	
Audio Response (300-3000Hz)	+1 to -3dB	
Conducted Spurious Emission	-57dBm < 1Ghz / -47dBm > 1Ghz / FCC Part 15	

\* Availability subject to country's laws and regulations. Radios meet applicable regulatory requirements.  
All specifications subject to change without notice. Specifications are not representative of all radios and may vary in different radios.

# Not applicable to Low Band

## Portable Military Standards 810 C, D, E & F

Applicable MIL-STD	810C		810D		810E		810F	
	Methods	Procedures	Methods	Procedures	Methods	Procedures	Methods	Procedures
Low Pressure	500.1	1	500.2	2	500.3	2	500.4	2
High Temp	501.1	1, 2	501.2	1, 2	501.3	1, 2	501.4	1, 2
Low Temp	502.1	1	502.2	1, 2	502.3	1, 2	502.4	1, 2
Temp. Shock	503.1	1	503.2	1	503.3	1	503.4	1
Solar Radiation	505.1	1	505.2	1	505.3	1	505.4	1
Rain	506.1	1, 2	506.2	1, 2	506.3	1, 2	506.4	1, 3
Humidity	507.1	2	507.2	2, 3	506.3	1, 2	507.4	-
Salt Fog	509.1	1	509.2	1	509.3	1	509.4	-
Dust	510.1	1	510.2	1	510.3	1	510.4	1
Vibration	514.2	8, 10	514.3	1	514.4	1	514.5	1
Shock	516.2	1, 2, 5	516.3	1, 4	516.4	1, 4	516.5	1, 4

### Factory Mutual Approval

GP328 radio units are certified by Factory Mutual Approvals as intrinsically safe for use in Division 1, Class I, II, III, Groups C, D, E, F, G and Division 2, Class I, Groups A, B, C, D, when ordered with the Factory Mutual approval battery option.

### Motorola: Reliability & Quality



Accelerated Life Testing  
Stringent Motorola Accelerated Life Testing  
simulating five years of hard use in real life.



MIL-STD 810C, D, E and F  
Stamp of approval from the U.S. Military for use in  
rough environments.



ISO 9001 Standard  
Compliance with ISO 9001 Standard – an international  
quality system assurance on design, development,  
production, installation and servicing of a product.



**Motorola Electronics Pte Ltd**

Motorola Innovation Centre, Level 7, Ang Mo Kio Street 64, Ang Mo Kio Industrial Park 3, Singapore 569088

[www.motorola.com/governmentandenterprise](http://www.motorola.com/governmentandenterprise)

MOTOROLA and the Stylized M Logo are trademark of Motorola, Inc. All other product or service names are property of their respective owners.  
©2009 Motorola. All rights reserved.

AC3-04-004 Rev.8